

Extreme 100 Unleaded Race Fuel

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: : Extreme 100

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel

1.3. Details of the supplier of the safety data sheet

F&L Racing Fuels
1635 W Gaylord St
Long Beach, CA 90813

1.4. Emergency telephone number

(562) 432-3946

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 1	H224
Acute Tox. 4 (Dermal)	H312
Acute Tox. 4 (Inhalation)	H332
Skin Irrit. 2	H315
Muta. 1B	H340
Carc. 1A	H350
Repr. 2	H361
STOT SE 3	H336
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H224 - Extremely flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H312+H332 - Harmful in contact with skin or if inhaled
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H340 - May cause genetic defects
H350 - May cause cancer
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting/equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P264 - Wash thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment

Extreme 100 Unleaded Race Fuel

Safety Data Sheet

P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P310 - IF SWALLOWED: immediately call a POISON CENTER or doctor/physician
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing
P308+P313 - IF exposed or concerned: Get medical advice/attention
P312 - Call a POISON CENTER/doctor/physician if you feel unwell
P314 - Get medical advice and attention if you feel unwell
P331 - If swallowed, do NOT induce vomiting
P332+P313 - If skin irritation occurs: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: Use CO2, dry chemical, foam (AFFF/ATC) or water spray for extinction
P391 - Collect spillage
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Naphtha, petroleum, full-range alkylate, butane-containing	(CAS No) 68527-27-5	60 - 80	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Methyl tert-butyl ether	(CAS No) 1634-04-4	0 - 30	Flam. Liq. 2, H225
Diisopropyl ether	(CAS No) 108-20-3	0 - 30	Not classified
Toluene (Component)	(CAS No) 108-88-3	5 - 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	0 - 20	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Ethyl alcohol (Component)	(CAS No) 64-17-5	0 - 15	Flam. Liq. 2, H225 Carc. 1A, H350
Isopentane	(CAS No) 78-78-4	5 - 10	Flam. Liq. 1, H224 STOT SE 3, H336 Asp. Tox. 1, H304

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air. If not breathing, administer CPR or artificial respiration. Get immediate medical attention.
- First-aid measures after skin contact : After contact with skin, wash immediately with plenty of water and soap. If skin reddening or irritation develops, seek medical attention.
- First-aid measures after eye contact : Immediately flush the eyes with plenty of water for at least 15 minutes while holding eyelids apart to ensure flushing of the entire surface of the eye. Continue flushing for an additional 15 minutes if a physician is not immediately available. Seek medical attention, preferably an ophthalmologist, immediately.

Extreme 100 Unleaded Race Fuel

Safety Data Sheet

First-aid measures after ingestion : If the material is swallowed, get immediate medical attention or advice. DO NOT induce vomiting unless directed to do so by medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : Breathing high concentrations may be harmful. May cause central nervous system depression or effects. Symptoms may include headache, excitation, euphoria, dizziness, incoordination, drowsiness, light-headedness, blurred vision, fatigue, tremors, convulsions, loss of consciousness, coma, respiratory arrest and death, depending on the concentration and duration of exposure. Breathing high concentrations of this material, for example, in a confined space or by intentional abuse, can cause irregular heartbeats which can cause death.

Symptoms/injuries after skin contact : Contact may cause reddening, itching and inflammation.

Symptoms/injuries after eye contact : Contact may cause pain and severe reddening and inflammation of the conjunctiva. Effects may become more serious with repeated or prolonged contact.

Symptoms/injuries after ingestion : May cause irritation of the mouth, throat and gastrointestinal tract. May cause central nervous system depression or effects. Symptoms may include salivation, pain, nausea, vomiting and diarrhea. Exposure may also cause central nervous system symptoms similar to those listed under "Inhalation"

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : CO2, dry chemical, foam (AFFF/ATC) or water spray

Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable liquid and vapor.

Explosion hazard : In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Vapors may travel long distances along ground before igniting/flashing back to vapor source.

5.3. Advice for firefighters

Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : If possible, stop flow of product.

Methods for cleaning up : Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillage into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4. Reference to other sections

No additional information available

Extreme 100 Unleaded Race Fuel

Safety Data Sheet

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements. Use appropriate grounding and bonding practices. Store in properly closed containers that are appropriately labeled and in a cool well-ventilated area. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues. Avoid skin contact. Exercise good personal hygiene including removal of soiled clothing and prompt washing with soap and water.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

7.3. Specific end use(s)

Fuel

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methyl tert-butyl ether (1634-04-4)

USA ACGIH	ACGIH TWA (ppm)	50 ppm
-----------	-----------------	--------

Diisopropyl ether (108-20-3)

USA ACGIH	ACGIH TWA (ppm)	250 ppm
USA ACGIH	ACGIH STEL (ppm)	310 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2100 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm

Toluene (108-88-3)

USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm

Xylenes (o-, m-, p- isomers) (1330-20-7)

USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Ethyl alcohol (64-17-5)

USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Isopentane (78-78-4)

USA ACGIH	ACGIH TWA (ppm)	600 ppm
-----------	-----------------	---------

8.2. Exposure controls

Appropriate engineering controls : Local exhaust and general ventilation must be adequate to meet exposure standards.
Hand protection : Wear impervious gloves to minimize skin contact.
Eye protection : Safety glasses. Wear splash goggles if splashing is likely.
Skin and body protection : Wear suitable working clothes.

Extreme 100 Unleaded Race Fuel

Safety Data Sheet

Respiratory protection : If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Clear
Odor : Strong hydrocarbon
Odor threshold : No data available
pH : Neutral
Relative evaporation rate (butylacetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : 90 - 437 °F
Flash point : -50 °F
Self ignition temperature : 495 °F
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : 3 - 4
Specific gravity : 5.9 - 6.3 lb/gal
Solubility : Negligible.
Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : 1.4 - 7.6 vol %

9.2. Other information

VOC content : 100 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Heat, flames, and other ignition sources.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Combustion produces carbon monoxide, aldehydes, aromatic and other hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful in contact with skin. Harmful if inhaled.

Naphtha, petroleum, full-range alkylate, butane-containing (68527-27-5)

LD50 oral rat > 7000 mg/kg

Extreme 100 Unleaded Race Fuel

Safety Data Sheet

Naphtha, petroleum, full-range alkylate, butane-containing (68527-27-5)	
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.04 mg/l/4h
Methyl tert-butyl ether (1634-04-4)	
LD50 oral rat	4 g/kg
LD50 dermal rabbit	> 10000 mg/kg
LC50 inhalation rat (ppm)	23576 ppm/4h
ATE US (oral)	4000000.00000000 mg/kg
Diisopropyl ether (108-20-3)	
LD50 oral rat	4700 mg/kg
LD50 dermal rabbit	20 ml/kg
ATE US (oral)	4700.00000000 mg/kg
ATE US (dermal)	20000.00000000 mg/kg
Toluene (108-88-3)	
LD50 oral rat	636 mg/kg
LD50 dermal rabbit	8390 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h
ATE US (oral)	636.00000000 mg/kg
ATE US (dermal)	8390.00000000 mg/kg
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	4300 mg/kg
LC50 inhalation rat (mg/l)	47635 mg/l/4h
ATE US (oral)	4300.00000000 mg/kg
ATE US (dermal)	1100.00000000 mg/kg
Ethyl alcohol (64-17-5)	
LC50 inhalation rat (mg/l)	124.7 mg/l/4h
ATE US (oral)	7060.00000000 mg/kg
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
Methyl tert-butyl ether (1634-04-4)	
IARC group	3 - Not classifiable
Toluene (108-88-3)	
IARC group	3 - Not classifiable
Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable
Ethyl alcohol (64-17-5)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure. Affected organs include: blood, kidneys, reproductive system, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.
Aspiration hazard	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Extreme 100 Unleaded Race Fuel

Safety Data Sheet

Naphtha, petroleum, full-range alkylate, butane-containing (68527-27-5)	
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Mysidopsis bahia)
Methyl tert-butyl ether (1634-04-4)	
LC50 fish 1	672 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	542 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	> 800 mg/l (Exposure time: 72 h - Species: Desmodemus subspicatus)
LC50 fish 2	929 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 other aquatic organisms 2	184 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
Diisopropyl ether (108-20-3)	
LC50 fish 1	91.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	190 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	7000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Toluene (108-88-3)	
LC50 fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 other aquatic organisms 1	> 433 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 2	12.5 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
Ethyl alcohol (64-17-5)	
LC50 fish 1	12.0 - 16.0 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Isopentane (78-78-4)	
EC50 Daphnia 1	2.3 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Methyl tert-butyl ether (1634-04-4)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	1.06 (at 23 °C)
Diisopropyl ether (108-20-3)	
Log Pow	1.52 (at 20 °C)
Toluene (108-88-3)	
Log Pow	2.65
Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF fish 1	0.6 - 15
Log Pow	2.77 - 3.15
Ethyl alcohol (64-17-5)	
Log Pow	-0.32
Isopentane (78-78-4)	
Log Pow	3.2 - 3.3

Extreme 100 Unleaded Race Fuel

Safety Data Sheet

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1203 Gasoline (includes gasoline mixed with ethyl alcohol, with not more than 10% alcohol), 3, II

UN-No.(DOT) : 1203

DOT NA no. : UN1203

DOT Proper Shipping Name : Gasoline
includes gasoline mixed with ethyl alcohol, with not more than 10% alcohol

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter.
177 - Gasoline, or, ethanol and gasoline mixtures, for use in internal combustion engines (e.g., in automobiles, stationary engines and other engines) must be assigned to Packing Group II regardless of variations in volatility.
B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.
B33 - MC 300, MC 301, MC 302, MC 303, MC 305, MC 306, and DOT 406 cargo tanks equipped with a 1 psig normal vent used to transport gasoline must conform to Table I of this Special Provision. Based on the volatility class determined by using ASTM D 439 and the Reid vapor pressure (RVP) of the particular gasoline, the maximum lading pressure and maximum ambient temperature permitted during the loading of gasoline may not exceed that listed in Table I.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.

Extreme 100 Unleaded Race Fuel

Safety Data Sheet

SECTION 15: Regulatory information

15.1. US Federal regulations

Methyl tert-butyl ether (1634-04-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on SARA Section 313 (Specific toxic chemical listings)

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %

Toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

15.2. US State regulations

Toluene (108-88-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	Yes	Yes		

Ethyl alcohol (64-17-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes			

Methyl tert-butyl ether (1634-04-4)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Diisopropyl ether (108-20-3)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Toluene (108-88-3)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Xylenes (o-, m-, p- isomers) (1330-20-7)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Ethyl alcohol (64-17-5)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Extreme 100 Unleaded Race Fuel

Safety Data Sheet

Isopentane (78-78-4)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases: see section 16:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Flam. Liq. 1	Flammable liquids Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Muta. 1B	Germ cell mutagenicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product